U.S. Oil Co., Inc.

Analytical Laboratory

425 S. Washington St. Combined Locks, WI 54113 Phone 920-735-8298

PRODUCT NO .:

110

MATERIAL SAFETY DATA SHEET

PRODUCT TRADE NAME:

THP Fluid

GENERIC/CHEMICAL NAMES:

PREPARATION/REVISION DATE:

07/28/99

REVISED FROM (DATE):

03/12/98

EMERGENCY PHONE #:

(920)-735-8298

NFPA CODE:

Health: 1

Fire: 1 Reactivity:

HMIS CODE:

Health: NE

Fire: NE

Reactivity:

NΕ

SECTION 1 - HAZARDOUS INGREDIENTS

This material is not known to contain greater than 0.1% of any carcinogen required to be listed under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Component

Cas #

OSHA PEL

ACGIH TLV

Distillate solvent dewaxed oils

64742-65-0

5 ma/m³

5 ma/m³

SECTION 2 - FIRE AND EXPLOSION HAZARDS

FLASH POINT:

> 400 °F

UPPER FLAMMABLE LIMIT: 10% (Estimated value)

LOWER FLAMMABLE LIMIT:

1% (Estimated value)

EXTINGUISHING MEDIA:

CO₂, dry chemical, foam (This combustible material has the burning characteristics of a high flash point mineral oil.

SPECIAL FIRE FIGHTING PROCEDURES:

Wear self contained breathing apparatus with full face piece. Cool exposed containers with water spray. Avoid breathing fumes.

UNUSUAL FIRE & EXPLOSION HAZARDS:

Toxic fumes may be evolved on burning or exposure to heat. Pressure may increase in overheated closed containers. Store below 120°F.

« ACUTE EXPOSURE »

ORAL TOXICITY:

Low order of acute oral toxicity. Aspiration into the lungs during ingestion or

vomiting may cause mild to severe pulmonary injury and possibly death.

EYE IRRITATION:

Product contacting the eyes may cause eye irritation. Based on data from

components or similar material.

SKIN IRRITATION:

Not expected to be a primary skin irritant. Based on data from components or similar materials. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying,

defatting and cracking of the skin.

DERMAL TOXICITY:

Product has a low order of acute dermal toxicity. Based on data from

components or similar materials.

INHALATION TOXICITY:

No data available to indicate product or components may be a toxic

inhalation hazard.

RESPIRATORY IRRITATION: If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract similar to that observed with mineral oil. Based on data from components or similar materials. Under good industrial hygiene practices where all exposure limits are observed respiratory irritation

should not be a problem.

DERMAL SENSITIZATION:

No data available to indicate product or components may be a skin

sensitizer.

INHALATION SENSITIZATION: No data available to indicate product or components may be a

respiratory sensitizer.

« CHRONIC EXPOSURE »

CHRONIC TOXICITY: No data available to indicate product or components present at greater than 1%

are chronic health hazards.

CARCINOGENICITY:

No data available to indicate any components present at greater than 0.1% may

present a carcinogenic hazard.

MUTAGENICITY:

No data available to indicate product or any components present at greater than

0.1% are mutagenic or genotoxic.

REPRODUCTIVE TOXICITY:

No data available to indicate either product or components present a

greater than 0.1% that may cause reproductive toxicity.

TERATOGENICITY:

No data available to indicate either product or components contained at greater

than 0.1% may cause birth defects.

« ADDITIONAL INFORMATION »

OTHER:

No other health hazards known.

EXPOSURE LIMITS:

See Hazardous Ingredients Section for any applicable exposure limits for

components.

SECTION 3A - EMERGENCY FIRST AID PROCEDURES

SKIN:

Remove contaminated clothing, wipe off excess then wash with soap and water. Get

medical attention if irritation develops.

EYE:

Flush with water at least 15 minutes. Get medical attention if eye irritation develops or

persists.

INHALATION:

Remove exposed person to fresh air if adverse effects are observed. Administer

oxygen if breathing is difficult. Give artificial respiration if breathing has stopped.

ORAL:

<u>DO NOT INDUCE VOMITING!</u> If conscious, give 2 glasses of water. Get immediate

medical attention. Material is considered low in acute oral toxicity.

ADDITIONAL:

Note to physician: treat symptomatically.

This material is not listed as a carcinogen by the NTP, IARC or OSHA.

SECTION 4 - SPECIAL PROTECTION INFORMATION

GLOVE PROTECTION:

Neoprene or Nitrile Gloves Recommended.

EYE PROTECTION:

Safety glasses recommended.

RESPIRATORY PROTECTION:

Normally not required, mask or respiratory for mists.

CLOTHING RECOMMENDATION:

As needed to prevent repeated or prolonged contact.

SECTION 5 - PHYSICAL DATA

VAPOR PRESSURE:

Less than 0.01 mm Hg @ 20 C

Essentially Neutral

SPECIFIC GRAVITY:

0.88-0.89 Insoluble

WATER SOLUBILITY:

PERCENT VOLATILE: Negligible from open container in 4 hours @ 38 C (100 F)

VAPOR DENSITY:

Greater than 1 (Air = 1)

EVAPORATION RATE: Less than 0.01 (@1 ATM and 25 C. n-butyl acetate = 1)

ODOR:

Mild Petroleum oil like

APPEARANCE:

Amber Viscous Liquid

SECTION 6 - STABILITY

STABILITY:

Stable at room temperature.

INCOMPATIBILITY:

Oxidizing agents and acids.

POLYMERIZATION:

Will not occur.

THERMAL DECOMPOSITION:

Smoke, carbon monoxide, aldehydes and other products of incomplete combustion. Under combustion conditions, oxides of the following elements will be formed: Calcium, Phosphorus, Sulfur, Zinc, carbon monoxide, hydrogen sulfide, and carbon

monoxide compounds.

SECTION 7 - SPILL OR LEAK PROCEDURES

SPILL PROCEDURES: Prevent entry into sewers and waterways. Pick up free liquid for recycle or

disposal. Absorb small amounts with an inert material.

WASTE DISPOSAL: Dispose of waste by supervised incineration in compliance with applicable laws

and regulations. Dispose of waste at an appropriate waste disposal facility in

accordance with current applicable laws and regulations, and product

characteristics at time of disposal.

SECTION 8 - SPECIAL PRECAUTIONS

SPECIAL PRECAUTIONS:

Keep containers closed when not in use. Do not handle or store near high heat or flames. Avoid breathing oil mists, wash skin thoroughly with

soap and water after handling.

SECTION 9 - TRANSPORTATION AND OSHA LABELING INFORMATION

TRANSPORTATION INCIDENT INFORMATION: For further information relative to spills resulting from transportation incidents, refer to latest Department of Transportation Emergency Response Guidebook for Hazardous Materials Incidents.

U.S. DOT HAZARDOUS MATERIALS SHIPPING DESCRIPTION:

Not Regulated.

OSHA REQUIRED LABEL INFORMATION: In compliance with hazard and right-to-know requirements, where applicable OSHA Hazard Warnings may be found on the label, bill of lading or invoice accompanying this shipment.

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of seller's knowledge, however, seller makes no warranty whatsoever, expressed, implied or of merchantability regarding the accuracy of such data or the results to be obtained from the use thereof, seller assumes no responsibility for injury to buyer or to third persons or for any damage to any property and buyer assumes all such risks.

N.A. = Not Applicable N.D. = Not Determine N.E. = Not Established